



Multifunction Meters

Transducers & Isolators

Temperature Controllers

Converters & Recorders

Digital Panel Meters

Current Transformers

Analogue Panel Meters

Shunts

Digital Multimeters

Clamp Meters

Insulation Testers

EARTH LEAKAGE RELAY CORE BALANCE CURRENT TRANSFORMER (CBCT)

Models

- CBCT - 73/30(50)
- CBCT - 95/50(40)
- CBCT - 135/85(30)
- CBCT - 165/130(30)

Features


- Slim design
- Encapsulated CBCT
- Compact in size
- Light in weight

SUBJECT TO CHANGE WITHOUT NOTICE

This manual superseded all previous versions – please keep for future reference

CBCT Specifications:

CBCT Type	Closed Toroid	System Frequency	50 Hz or 60 Hz
Turns Ratio	600 / 1A	Insulation Voltage	3kV for 1 minute
Rated Current	30A	Distance Between CBCT and ELR	< 1 meters
System Voltage	720 V maximum	Operating Temperature	10°C to +55°C

CBCT Dimensions


Dimensions in mm				
CBCT	OD	ID	Axial	Current Ranges
CBCT - 73/30(50)	73	30	50	30mA to 30A
CBCT - 95/50(40)	95	50	40	30mA to 30A
CBCT - 135/85(30)	135	85	30	30mA to 30A
CBCT - 165/130(30)	165	130	30	500mA to 30A

CBCT Ordering Information:

CBCT	Description
CBCT 73	CBCT - 73/30(50)
CBCT 95	CBCT - 95/50(40)
CBCT 135	CBCT - 135/85(30)
CBCT 165	CBCT - 165/130(30)

CBCT Ordering Information:

- 1] CBCT 73 -2 :-
CBCT - 73/30(50), Quantity Two.
- 2] CBCT 165 -1 :-
CBCT - 165/130(30), Quantity One.

Contact

Sifam Tinsley Instrumentation Ltd

1 Warner Drive
 Springwood Industrial Estate
 Braintree, Essex
 CM7 2YW

Tel: 01376 335271
 E-mail: sales@sifamtinsley.com

www.sifamtinsley.co.uk