



Theta 30P

Theta 30- Power Transducer with Display

Product Code	TT30-	X	X	XX	XX	X	X	X	X	X	XX
Input Signal	Active Power Active P	P									
	Reactive Power Reactive Q	Q									
	Apparent Power Apparent S	S									
Network	1P2W		1								
	3WUB		2								
	4WUB		3								
	4WB		4								
	3WB		5								
	3WB - U12		6								
	3WB - U13		7								
	3WB - U23		8								
Input Range	100-500V			8F							
Input Current	1/5A				75						
	1/5A 400Hz				76						
Power Supply	60-300V AC/DC					H					
	24-60V AC/DC					F					
Output	1 O/P 10						1				
	2 O/P 20						2				



Display Module	With Display D								D				
	Without Display WD								Z				
RS 485 Module	With RS 485 R									R			
	Without RS-485 Z									Z			
Prog.cable Version	With PRKAB 601 PRK P											C	
	Without PRKAB 601 Z											Z	
	Standard												00

Commonly used Ranges for Theta 30-

TT30-P38F75F2DRZ00	Power; 4Wire Unbal; Input: 100-500V, 1/5A AC; Aux:24-60VAC DC; 2Output; Display; RS485
TT30-P38F75H2DRZ00	Power; 4Wire; Unbal; Input: 100-500V 1/5A AC; Aux: 60-300VAC DC; 2Output; Display; RS485

