

## Part Number Coding Booklet

**Theta Series - P18D** 

## P18D- Temperature and Humidity Transducer with External Sensor

| Product Cod e    | P18D-                                 | Х | XX | Х | Х |
|------------------|---------------------------------------|---|----|---|---|
| Analog Outputs   | Without Analog Outputs                | 0 |    |   |   |
|                  | Current 4 20 mA                       | 1 |    |   |   |
|                  | Voltage 0 10 V                        | 2 |    |   |   |
| Version          | Standard                              |   | 00 |   |   |
|                  | On Order*                             |   | XX |   |   |
| Language         | Polish                                |   |    | Р |   |
|                  | English                               |   |    | E |   |
|                  | Other                                 |   |    | Х |   |
| Acceptance Tests | Without Additional Requirements       |   |    |   | 8 |
|                  | With a Quality Inspection Certificate |   |    |   | 7 |
|                  | Acc. to Customer's Agreement*         |   |    |   | Х |

## Commonly Used Ranges for P18D-

| P18D 100U0 | Aux: 9-24VAC/DC; O/P: RS485 & 2x 4-20mA with Sensor on Housing   |
|------------|--|
| P18D 400U0 | Aux: 9-24VAC/DC; O/P: RS485 & 2x 4-20mA with Sensor on 0.5m Wire |



Email: <u>psk@sifamtinsley.com</u> | Web: <u>www.sifamtinsley.com</u> Phone: 404.736.4903 | Fax: +1 678 881 0008 x 701 | Toll Free: 800 879 6171 3105 Creekside Village Dr, Unit 801, Kennesaw GA 30144