



Theta 50

Theta 50- DC signal Isolator

Product Code	TT50-	XX	XX	XX	X	XXXXXX
Input Range	0-10V	5H				
	2-10V	3C				
	1-5V	3B				
	0-20mA	32				
	1-5mA	53				
	4-20mA	55				
	0-75mV	3D				
Output Range 1	0-20mA		32			
	4-20mA		55			
	0-10V		5H			
	2-10V		3C			
Output Range 2	0-20mA			32		
	4-20mA			55		
	0-10V			5H		
	2-10V			3C		
	0-5V			3D		
Power Supply	60-300V AC/DC				H	
	24-60V AC/DC				F	
Version	Standard					000000



Commonly used codes for Theta 50-

TT50-3J5555H000000	Input: 0-50mV DC; Dual Output: 4-20mA DC; Aux: 60-300VACDC
TT50-3J5555F000000	Input: 0-50mV DC; Dual Output: 4-20mA DC; Aux: 24-60 VACDC
TT50-3K5555F000000	Input: +/-50mV DC; Dual Output: 4-20mA DC; Aux: 24-60VACDC
TT50-3K5555H000000	Input: +/-50mV DC; Dual Output: 4-20mA DC; Aux: 60-300VACDC
TT50-3G5555H000000	Input: 0-250V DC; Dual Output: 4-20mA DC; Aux: 60-300VACDC
TT50-55555HH000000	Input: 4-20mA DC; Output: 0-10V DC; Output: 4-20mA DC; Aux: 60-300VACDC
TT50-55555HF000000	Input: 4-20mA DC; Output: 0-10V DC; Output: 4-20mA DC; Aux: 24-60VACDC
TT50-5H5555HH000000	Input: 0-10V DC; Output: 4-20MA DC; Output: 0-10V DC; Aux: 60-300VACDC
TT50-5H5555HF000000	Input: 0-10V DC; Output: 4-20MA DC; Output: 0-10V DC; Aux: 24-60VACDC

